

 $Ball \mid 42 > Configure item number from attributes below.$

	Finish	Blade Span	Blade Color	Light Option	Control Option
#BAL	-	-	-	-	-
	•	•	•	•	^
	GW Gloss White	42 42" Span	WH White	NL No Light	001 Fan Speed Only
	BA Brushed Aluminum	n	AL Aluminum	652 20W LED	002 Fan & Light – 3 Wire
			MP Maple		003 Handheld Remote
					004 Fan & Light – 2 Wire
					005 Wall/Remote Combo

42" -

Dimensions 9.5" & 15" w/ 6" down rod (shown) 19.5" & 25" w/ 16" down rod

Also available in 52" blade span.

Specifications

- 153mm x 18mm AC motor with reverse switch on fan body
- Die cast aluminum construction
- 42" span, plywood blades
- Includes 6" and 16" down rods (longer options also available)
- Optional LED light: 20W, 90 CRI, 3000K, 1800 lumens (dimmable) behind opal glass diffuser; CA Title 24, JA8-2019 compliant
- Slope compatible up to 33°; adapter available for slopes up to 45°
- Designed by Ron Rezek
- ETL listed for dry and damp locations
- Weight: 16 lbs (7.3 kgs)

Performance Data

LOWEST SPEED

RPM: 120 CFM: 1,765 Watts: 13.12 CFM/W: 134.53

HIGHEST SPEED

RPM: 270 CFM: 3,772 Watts: 58.22 CFM/W: 64.79

Energy Guide Data

Average Energy Use 36 Watts

> Average Airflow 2,831 CFM

Yearly Energy Cost \$10

Average Efficiency 78 CFM/Watt

^{*} Energy Guide Data represents weighted averages of low speed and high speed performance, assuming typical use (excluding light). For more information, visit www.modernfan.com.

Ball | 42



FAN FINISHES



PLYWOOD BLADES

Plywood blades are constructed of furniture grade veneers, painted or stained as shown here. Natural variations may exist in woodgrains and finishes.



BALL FAN CONTROLS

Selection of a control option is made at time of order and incorporated into the fan item number (except #FC-009A and #FC-009B which are sold as accessory items).



#FC-001 **Fan Speed Only Control** (no light)

For a single AC fan, providing four speeds. Not intended for a fan with light. Note: Not compatible with remote control.

Handheld Remote RF Control

Designed for independent operation

a single AC fan or AC fan with LED

light, providing three speeds and full

using only one circuit (two wires).

and comes with a wall mounting

range dimming (or "on/off" switching),

Includes RF handset, receiver, battery



Fan & Light Control-3 Wire

For a single AC fan with LED light. providing four speeds and dimming function. Requires three wires from switch location to fan. Note: Not compatible with remote control.



#FC-004-LED Fan & Light RF Control-2 Wire

Designed for independent operation of a single AC fan or AC fan with LED light, providing three speeds and full range dimming (or "on/off" switching), using only one circuit (two wires). Includes RF wall control (with master power switch), switch plate and receiver.



#FC-009A / #FC-009B

Sold as an accessory item, providing three speeds for multiple AC fans on a single switch leg. FC-009A for 2-3 fans FC-009B for 3-6 fans

Note: Not compatible with remote control. Control of fan lights must be accounted for separately with owner provided control on separate switch leg.



SLOPE ADAPTER

DOWN RODS

The Ball ships standard with 6" and 16"

down rods. Use the following part numbers to order accessory down rods.

Length

12 12"

24 24"

36 36"

48 48"

72 72"

60" 60

Finish

GW Gloss White

Brushed Aluminum

#DRD

The Ball will accommodate ceiling slopes up to 33 degrees. The #045 slope adapter can accommodate slopes exceeding 33 degrees and up to 45 degrees.



Finish

#045

GW Gloss White Brushed Aluminum

bracket for handset. #FC-005-LED Wall/Remote Combo

RF Control-2 Wire

(M)

#FC-003-LED

Designed for independent operation of a single AC fan or AC fan with LED light, providing three speeds and full range dimming (or "on/ off" switching), using only one circuit (two wires). Includes RF handset, RF wall control (with master power switch), switch plate and receiver.

Multi-fan Speed Controls for AC Fans

(no lights)

The Modern Fan Co. tel 541-482-8545 toll free 888-588-3267

email info@modernfan.com website modernfan.com