

 ${\sf Flow}\,>{\sf Configure}$ item number from attributes below.

	Finish	Blade Span	Blade Color	Light Option	Control Option
#FLO	-	-	-	-	-
	•	•	•	•	•
	GW Gloss White	52 52" Span	WH White	NL No Light	001 Fan Speed Only
	MN Matte Nickel		NK Nickel	372 20W LED	002 Fan & Light – 3 Wire
			BB Bamboo		003 Handheld Remote
					004 Fan & Light – 2 Wire
					005 Wall/Remote Combo

Specifications

- 153mm x 18mm AC motor with reverse switch on fan body
- Die cast aluminum construction
- 52" span, formed plywood blades
- Includes 4.5" and 16" down rods (longer options also available)
- Optional LED light: 20W, 90 CRI, 3000K, 1800 lumens (dimmable) behind opal glass diffuser; adds .5" to length of fan; CA Title 24 (JA8) compliant
- Slope compatible up to 33°; adapter available for slopes up to 45°
- Designed by Ron Rezek
- ETL listed for dry and damp locations
- Weight: 19 lbs (8.6 kgs)

Performance Data

LOWEST SPEED

RPM: 65 CFM: 1,524 Watts: 10.88 CFM/W: 140

HIGHEST SPEED

RPM: 200 CFM: 5,350 Watts: 70.98 CFM/W: 75

Energy Guide Data

Average Energy Use 43 Watts

> Average Airflow 3,572 CFM

Yearly Energy Cost \$12

Average Efficiency 82 CFM/Watt

Energy Guide Data represents weighted averages of low speed and high speed performance, assuming typical use (excluding light). For more information, visit www.modernfan.com.

Flow



FAN FINISHES



PLYWOOD BLADES

Plywood blades are constructed of furniture grade veneers, painted or stained as shown here. Natural variations may exist in woodgrains and finishes.



FLOW FAN CONTROLS

Selection of a control option is made at time of order and incorporated into the fan item number (except #FC-009A and #FC-009B which are sold as accessory items).



#FC-001 Fan Speed Only Control (no light)

For a single AC fan, providing four speeds. Not intended for a fan with light. Note: Not compatible with remote control.

#FC-003-LED



Fan & Light Control-3 Wire

For a single AC fan with LED light. providing four speeds and dimming function. Requires three wires from switch location to fan. Note: Not compatible with remote control.



#FC-004-LED Fan & Light RF Control-2 Wire

Designed for independent operation of a single AC fan or AC fan with LED light, providing three speeds and full range dimming (or "on/off" switching), using only one circuit (two wires). Includes RF wall control (with master power switch), switch plate and receiver.



#FC-009A / #FC-009B **Multi-fan Speed Controls** for AC Fans

(no lights)

Sold as an accessory item, providing three speeds for multiple AC fans on a single switch leg. FC-009A for 2-3 fans FC-009B for 3-6 fans

Note: Not compatible with remote control. Control of fan lights must be accounted for separately with owner provided control on separate switch leg.



range dimming (or "on/off" switching), using only one circuit (two wires). Includes RF handset, receiver, battery and comes with a wall mounting bracket for handset.

Handheld Remote RF Control

Designed for independent operation

a single AC fan or AC fan with LED

light, providing three speeds and full



#FC-005-LED Wall/Remote Combo RF Control-2 Wire

Designed for independent operation of a single AC fan or AC fan with LED light, providing three speeds and full range dimming (or "on/ off" switching), using only one circuit (two wires). Includes RF handset, RF wall control (with master power switch), switch plate and receiver.

DOWN RODS

The Flow ships standard with 4.5" and 16" down rods. Use the following part numbers to order accessory down rods.

	Finis	sh	Len	Length	
#DRD	-		-		
	•		•		
	GW	Gloss White	12	12"	
	MN	Matte Nickel	24	24"	
			36	36"	
			48	48"	
			60	60"	
			72	72"	

SLOPE ADAPTER

The Flow will accommodate ceiling slopes up to 33 degrees. The #045 slope adapter can accommodate slopes exceeding 33 degrees and up to 45 degrees.

Finish #045

GW Gloss White MN Matte Nickel